

Technical Data Sheet (TDS)

1. Product Overview

- Product Name: 硫代硫酸钠 - English Name: Sodium Thiosulfate (Anhydrous) - CAS Number: 7779-89-3 - Formula: $\text{Na}_2\text{S}_2\text{O}_3$ - Molecular Weight: 158.11 g/mol - Product Characteristics: High-purity inorganic sulfur compound with excellent chlorine removal, reduction and chelating performance; good water solubility (≥ 100 g/100 mL at 25°C); stable chemical properties under normal conditions; non-flammable, low toxicity; wide pH adaptation range (4.0-10.0); compatible with most water treatment agents and textile auxiliaries; suitable for water treatment, photography, medical treatment, textile and other industrial fields.

2. Technical Specifications (Complies with GB/T 637-2006)

Item	Specification
Appearance	White crystalline powder, no mechanical
Purity (by Titration)	$\geq 99.0\%$
Melting Point Range	48-52°C
Ash Content	$\leq 0.1\%$
Moisture Content (105°C, 2h)	$\leq 0.3\%$
pH Value (25°C, 1% Aqueous)	6.0-8.0
Chloride (Cl^-) Content	$\leq 0.005\%$
Heavy Metals (Pb) Content	$\leq 0.0005\%$
Solubility in Water (25°C)	≥ 100 g/100 mL
Chlorine Removal Rate (25°C, 10)	$\geq 99.0\%$
Operating pH Range	4.0-10.0

3. Product Advantages

1. Excellent Chlorine Removal Performance: Rapidly reacts with free chlorine and combined chlorine in water (reaction rate constant $\geq 10^6$ L/(mol·s)); chlorine removal rate $\geq 99.0\%$ at standard dosage; suitable for drinking water and industrial water treatment. 2. Strong Reduction & Chelating Ability: Effectively reduces oxidizing substances (chlorine, ozone, permanganate) in water; forms stable chelates with heavy metal ions (copper, iron, lead) (chelation constant $\geq 10^8$); removes heavy metal contaminants. 3. Good Water Solubility: Easily soluble in water (≥ 100 g/100 mL at 25°C); dissolves quickly without residue; convenient for preparation of aqueous solutions and on-site dosing. 4. Wide pH Adaptation Range: Effective in acidic, neutral and slightly alkaline environments (pH 4.0-10.0); no need for additional pH adjustment in most application scenarios; stable performance in complex water quality.

4. Application Fields

- Water Treatment Industry: Chlorine remover for drinking water, swimming pool water, industrial cooling water and wastewater treatment; reduces residual chlorine to protect reverse osmosis membranes and water treatment equipment; chelating agent for heavy metal removal in wastewater. - Photography Industry: Photographic fixer (hypo); dissolves unexposed silver halide in photographic emulsions; improves image clarity and stability; used in film and photo developing processes. - Medical Industry: Antidote for cyanide poisoning



NEWAY SINOPHC TECH. LIMITED

ADD:RM. 204, BUILDING 3, NO. 188, AONA RD., CHINA (SHANGHAI) PILOT FREE TRADE ZONE.
Email:marketing01@newayphc.com; Phone:+86-021-50350029 <https://www.newayphc.com>

(combines with cyanide to form non-toxic thiocyanate); treatment of nitrate and nitrite poisoning; topical anti-inflammatory agent for skin wounds.

5. Usage Methods

- Dosage (as pure product): - Water Treatment (Chlorine Removal): 1.5-2.0 mg/L per 1 mg/L residual chlorine; adjust dosage based on residual chlorine content. - Photography (Fixer): 200-300 g/L aqueous solution; soak photos/films for 5-10 minutes. - Medical (Antidote): Intravenous injection, dosage based on patient weight (0.1-0.2 g/kg); administered by professional medical personnel. - Textile Industry (Chlorine Removal): 0.5-1.0 g/L aqueous solution; soak textiles for 10-15 minutes after bleaching. - Usage: Dissolve the product in water (dissolution ratio 1:10) to prepare a stock solution, then dilute to the required concentration and add to the system; stir evenly after dosing to ensure full reaction. - Optimal Conditions: Use at temperature 10-40°C and pH 4.0-10.0; reaction time \geq 5 minutes for chlorine removal; avoid mixing with concentrated acids directly (dilute first if necessary).

6. Packaging & Storage

- Packaging Specifications: 25 kg paper-plastic composite bags (with inner PE liner); 50 kg plastic drums; 200 kg iron drums (lined with PE bag); custom packaging available upon request. - Storage Conditions: Store in cool, dry, well-ventilated warehouse (5-35°C); keep container tightly closed to prevent moisture absorption, dust contamination, and caking; avoid direct sunlight and high temperature ($>50^{\circ}\text{C}$); store separately from concentrated acids, oxidizing agents, and food-grade materials; stack bags/drums stably (no more than 4 layers for bags, 2 layers for drums) to prevent tipping and damage; keep away from children and pets. - Shelf Life: 36 months (unopened, specified conditions); use promptly after opening, seal tightly after each use; do not use if caking, discoloration (turning yellow), or moisture absorption occurs.

7. Safety & Protection

- The product is a non-flammable solid, mildly irritating to skin, severely irritating to eyes, toxic to aquatic organisms; reacts with concentrated acids to release irritating sulfur dioxide gas. - Operators must wear personal protective equipment: dust mask, chemical-resistant gloves (rubber or nitrile), safety goggles; avoid skin and eye contact, and inhalation of dust. - Operate in well-ventilated area; install emergency eyewash stations nearby; in case of leakage, follow accidental release measures to avoid environmental contamination (especially aquatic ecosystems). - In case of skin contact: Rinse with plenty of running water for at least 10 minutes immediately, remove contaminated clothing; no special treatment required for mild irritation. - In case of eye contact: Rinse with clean water or normal saline for at least 15 minutes immediately, do not rub eyes, and seek emergency medical help immediately if irritation persists.

8. Quality Assurance

- Manufactured in accordance with ISO 9001 quality management system standards; strictly controls raw materials (sodium sulfite, sulfur), production processes (synthesis, purification, crystallization), and finished product testing. - Each batch of product is strictly tested with a Certificate of Analysis (COA) to meet GB/T 637-2006 and international quality standards, ensuring product purity, performance, and safety. - Provide professional technical support: customize dosage and application schemes based on user system parameters (water quality, temperature, application scenario); provide on-site guidance for product use, dosage adjustment, and problem-solving; solve water treatment, textile bleaching and other application problems in a timely manner.